



Economy Test Plug

Low Pressure Testing of Pipe & Tubing

Key Features

- Durable carbon steel construction
- Replaceable neoprene seals
- Long wearing full disk seals extend the life of the plug

Technical Documents

- [DC2650 - Economy Test Plug Operating Procedures](#)

Simple and reliable low pressure testing of pipe and tubing to 35 PsiG (2.4 BarG). Economy plugs feature a neoprene seal - the only part of the plug that comes in contact with the tube I.D.

Simply install the Economy Test Plug into the open end of a pipe and/or tube, and tighten to expand the seal.

Pressure Rating

- Up to 35 PsiG (2.4 BarG)

Size Range

- 3/8" to 4" (9.525-101.6mm)

Standard Materials

- Zinc plated Carbon Steel, Neoprene seals



North, Central & South America

2701 Township Line Rd
Hatfield, PA 19440

T: (+1) 215.721.1100 | (+1) 1.800.355.7044
E: est-info@curtisswright.com

Europe, Middle East, Africa (EMEA)

Hoorn 312D, 2404 HL Alphen aan den Rijn
The Netherlands

T: (+31) 172.418841
E: est-emea@curtisswright.com

Asia

Singapore
T: (+65) 3158.5052
E: est-asia@curtisswright.com

Korea

+82.10.9279.7132
est-asia@curtisswright.com

valves.curtisswright.com/EST

Economy Test Plug

©2026 Curtiss-Wright - All rights reserved. Specifications are subject to change without notice. All trademarks are property of their respective owners. I MK0035_06.2026

